

SALINA LIMITED COMPANY

SALI TILE ADHESIVE

SALI TILE ADHESIVE is a cement based tile glue for large ceramic wall and floor tiles interior or exterior application. SALI TILE ADHESIVE with superior flexibility and high grab to support even the heaviest of wall tiles.



www.salinagroup.com

COMPOSITION

Consisting Portland cement, filler, fine graded sand and chemical additives containing high organic polymer content for better bonding

PREPERATIONS

Ensure that the surface to be applied is clean and free of foreign matter. Remove all loose particles, mould oil and other contaminations from the surface to be applied. Surface should be moisture with clean water and allow to evaporate completely.

MIXING

SALI TILE ADHESIVE should be mix thoroughly with mechanical mixer or electrical hand stirrer in a clean container with approximately 25% water by weight. Add 5 liter clean water for 20 kg SALI TILE ADHESIVE. Mix up to getting uniform mix and should be allowed to stand for 5 – 10 minutes. After maturing stir again, no further water should be added. Mixed mortar should be used within 45 minutes.

APPLICATION

Apply the mix up to thickness of 3- 5 mm with notched trowel to the prepared surface. Fix the tile on applied glue and press after leveling. Ensure that each tile surface completely contact with adhesives. Do not spread more than 1 Sq. meter at a time. Tile should not be fixed on dry or set tile glue. Leave for at-least 24 hours before grouting.

To ensure even spacing, tile spacers of the required thickness are recommended. Clean tools and tile work with water while mortar is fresh.

GROUTING

Carefully attention must be paid to the grouting operation; otherwise satisfactory job will be seriously impaired. Grouting should not be used for at-least 2 days after completion of tiling. Use SALI TILE GROUT for better results.

PACKAGING

SALI TILE ADHESIVE is packed in 20 kg and 25 kg plastic bags. Available as custom packaged to suit specific job requirements.

STORAGE

Material should be stored in a dry covered area protected from elements. Unopened bags have a shelf of 12 months.

SAFETY PROCEDURES

Wear safety such as rubber gloves, dust mask and safety glasses used to handle conventional cement based products should be worn. In case of contact with eyes, rinse with plenty of water and seek medical advice accordingly. MSDS are available upon request.

TECHNICAL ASSISTANCE

For advice on how to use SALI TILE ADHESIVE product consult your nearest SALINA technical office.

COLORS

- » White
- » Grey

FEATURES

- » Excellent adhesion.
- » Water Resistant.
- » Improved workability.
- » Chemical and Oil resistant.
- » Economical contract packing.
- » Long open time & slip resistant.

USES

- » For porcelain, ceramic, mosaic and stone.
- » Suitable for dry and intermittently wet areas.
- » Interior and Exterior application.
- » Flexible, suitable for a variety of wall tiling projects.
- » For fixing wall tiles up to 400mm x 400mm on absorbent surfaces and, up to 300mm x 300mm ceramic tiles over existing tiling.

TECHNICAL DATA

Physical State	Mixed Granular Powder
Binder	Portland Cement
Color	Grey & White
Granular Size	0 – 0.4 mm
Water Requirement	25 % Approx.*
Yield	680 Lit./ Ton approx.*
Working Time	45 Min.*
Dry Density	1.40 Kg/L*
Compressive strength	15 N/mm ² @ 28 Days*
Flexural Strength	4 N/mm ² @ 28 days*
Bond Strength	1.5 N/mm ² @ 14 days*
Applicable Standards	BS EN 12004, Type C, ANSI A 118.1
Shelf Life	12 Months from Mfg. Date

* Test results as per laboratory conditions

Dubai

United Arab Emirates
Tel: +971 4 3232935
Fax: +971 4 3232936
P.O.Box 32143

Sharjah

United Arab Emirates
Tel: +971 6 7434488
Fax: +971 6 7434484
P.O.Box 23872

Doha

Qatar
Tel: +974 4 604075
Fax: +974 4 4604497
P.O.Box 40411

Cairo

Egypt
Tel: +205 5 2572094
Fax: ++205 5 2574776
P.O.Box 911 Heliopoes

Ontario

Canada
Tel: (+164) 79846479
Fax: (+190) 52324720
P.O.Box 958 Summerbreeze Crt. L5V 1C9