شركة سالينا المحدودة SALINA LIMITED COMPANY

Technical Data Sheet

Salina Spray Plaster-Fine (SSPF-230)

DESCRIPTION

Salina Spray Plaster- Fine is a pre-mixed skim coat plaster for uneven surface application. Provides smooth leveled surface over concrete or plastered surfaces for paint application. It can use for plaster undulations and repairing. Only add water to the dry mix and getting creamy constitution which have good workability and bonding.

COMPOSITION

Consisting Portland cement, Hydrated lime, high quality fillers and chemical improving agents, those ensuring good workability and bonding.

FEATURES& ADVANTAGES

- Easy application and Good workability.
- Extra smooth finishing.
- Water Resistant.
- Better bonding with variety of substrates.
- Interior or Exterior applications.

BACKGROUND PREPARATION

Remove all residual mould oil, dust, loose particles, flakes and other contaminations from the background to be applied. Spray clean water to the wall for kill the suction. Allow some time for free water to evaporate completely from the surface.

MIXING

Salina Spray Plaster- Fine should be mixed in clean container by using electrical hand stirrer to obtain perfect and homogenous mix. Only potable water should be added to achieve a creamy and workable thick plaster, approx 7.5 liters of water is required for each 20 kg bag. Leave the mix for 5 min for proper dissolving of additives. Mix again prior to application without addition of water. Harden or partially set material should not be used for mixing and mixed material should be used within hour.

COVERAGE

Approximately 10 m² per 20 kg bag @ 1mm thickness.**

 Dubai - U.A.E.
 Tel: +971 4 2671511
 Fax: +971 4 2671511
 Fax: +971 4 2671511
 P.O.Box: 32143

 Sharjah - U.A.E.
 Tel: +971 4 2671511
 Fax: +971 4 2671611
 P.O.Box: 32143
 Doha - Qatar
 : Tel.:+974 4604075
 Fax: +974 4604497
 P.O.Box: 40411

 Sharjah - U.A.E.
 Tel: +971 6 7434488
 Fax: +971 6 7434484
 P.O.Box: 32143
 Amman-Jordan
 : Tel.: +96264023239
 Fax: +96264023721
 P.O.Box: 564 ZIP: 11511

 Riyadh - K.S.A.
 Tel: +966 1 4984266
 Fax: +966 1 4984277
 P.O.Box: 5580 ZIP:11432
 Cairo - Egypt
 : Tel.: +2022616961
 Fax: +2024030526
 P.O.Box: 991 Heliopoles

 Roma - italy:
 : Tel: +39 06 25204557
 Fax: +39 06 21892189
 C.P. 114 13 Roma A
 Ontario - Canada: Tel.: +1 (519)253-5556
 1076 Walker Road Unit G

 Widsor - Ontario n8y 2n5 - Canada
 Widsor - Ontario n8y 2n5 - Canada
 Yes - Canada
 Yes - Canada

شــركــة سـالينا المحــدودة SALINA LIMITED COMPANY

APPLICATION

Salina Spray Plaster- Fine can be applied on prepared background by putty knife or spatula. Apply the filler as thin even layers. If the area under repair requires a thick coat then apply several thin layers allowing each layer to dry before adding the next. Lightly sand paper over the dry final surface before painting preferably within 24 hours of application. Finished plaster should be cure with potable water.

PACKAGING

Salina Spray Plaster- Fine is packed in 20 kg Plastic bags on pallets with shrink wrapping.

STORAGE

The material should be stored in a clean and dry environment protected from direct sunlight and extreme heat or cold. Unopened bags have a shelf life of 12 months from the date of manufacturing.

HEALTH AND SAFETY

Use under well ventilated conditions with safety essentials like mask, gloves and Safety glass. Do not breathe or inhale mist. Avoid skin contact; spillage on the skin should be immediately removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention must be sought immediately. MSDS available upon request.

TECHNICAL ASSISTANCE

For any technical support about product application, consult your nearest SALINA technical office or visit our website.

TECHNICAL DATA

Physical State	Mix Powder	Dry Density	1.1 Kg/ liter*			
Binder	Portland Cement	Wet Density	1.5 Kg/ liter*			
Color	Grey	Coverage	10 m ² /bag @1 mm Thickness**			
Granular Size	0 – 0.1 mm	Compressive Strength	10 N/mm ² @ 28 Days*			
Water requirement	30 %*	Flexural Strength	2.5 N/mm ² @ 28 Days*			
Packaging	20 Kg plastic Bag	Curing	Minimum 2 Days, 3 times/day			
Working Time	20 min Approx.*	Shelf life	12 Months from date of Mfg.			
Test Standards	BS 5262, BS5462, BS EN 13914-1 & 2					

*Test results as per laboratory conditions. **Coverage of plaster may vary with respect to wall perfection, thickness, wastages and applicator skill.

Dubai - U.A.E.	Tel: +971 4 2671511	Fax: +971 4 2671611	P.O.Box: 32143	Doha - Qatar : Tel.:+974 4604075 F	ax: +974 4604497	P.O.Box: 40411
Sharjah - U.A.E.	: Tel: +971 6 7434488	Fax: +971 6 7434484	P.O.Box: 32143	Amman-Jordan : Tel.: +96264023239 F	ax: +96264023721	P.O.Box: 564 ZIP: 11511
Riyadh - K.S.A.	: Tel: +966 1 4984266	Fax: +966 1 4984277	P.O.Box: 5580 ZIP:11432	Cairo - Egypt : Tel.: +2022616961 F	ax: +2024030526	P.O.Box: 991 Heliopoles
Roma - italy: : Tel: +39 06 25204557	Fax: +39 06 21892189	C.P. 114 13 Roma A	Ontario - Canada: Tel.: +1 (519)256-6555 F	fax: +1 (519)253-55	56 1076 Walker Road Unit C	
			Widsor - Ontario n8v 2n5 - Canada			