

SALINA LIMITED COMPANY



ATLAS GROUT
WATER PROOF GROUTING

◆◆

◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆

Grouting of ceramic walls & Floor tiles
Swimming pool tiles &
Decorative stone
and Marbles

◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆

صنع طبقاً لأعلى المواصفات البريطانية خصيصاً لمنطقة الشرق الأوسط والخليج
MANUFACTURED ACCORDING TO THE BRITISH SPECIFICATIONS
SPECIALLY FOR MIDDLE EAST & GULF AREA

DUBAI - U.A.E. TEL: 971-4-2671511, FAX: 04-2671611
MOBILE: 050 - 6466502, P.O. BOX: 32143
SHARJAH - U.A.E. TEL: 971-6-7447404, FAX: 06-7447101
MOBILE: 050-6466502, P.O. BOX: 23872
DOHA - QATAR TEL: 9744604075, FAX: 9744604497
MOBILE: 9745865845, P.O. BOX: 40411
CAIRO - EGYPT TEL: 0020 - 12 - 2211525
E-mail: salina99@emirates.net.ae

◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆◆

ATLAS TILE GROUT

ATLAS TILE GROUT is high performance cement based pre-mixed non-shrink grout, used for filling joints, in wet and dry areas.



www.salinagroup.com

COMPOSITION

Manufactured from specially selected cements, fillers, metal oxide color pigmentations and chemical improving agents.

PREPERATIONS

- » Before grouting confirm mortar of the adhesives has completely hardened. Verify that the waiting time indicated on the relevant technical data sheet has elapsed.
- » The joints must be clean from loose particles, dust and other contaminations.
- » Wet the joints with clean water when using very porous ceramic tiles in high temperatures and in the presence of wind.

MIXING

- » Each bag of ATLAS TILE GROUT mix with 3 liters of water in a clean container. Mix well with electrical spiral mixer to get uniform mix.
- » Let the mixture stand (slake) for 5minutes, and then remix and use.
- » Use the mixture within 2 hours of preparations.

APPLICATION

- » Apply ATLAS TILE GROUT with a rubber spatula into the joints diagonally by filling all the gaps, make sure that the product is well compacted with no voids. Use the product within a maximum 45 minutes (depending on temperature) after mixing.
- » Allow the grout to dry before starting the cleaning process, remove surplus with a damp of sponge moving diagonally to prevent removal of grout within the joints
- » Rinse the sponge frequently using two water containers, one to remove the grouts residue and the other one to clean the sponge.

STORAGE

Material should be stored in a dry covered area protected from elements. Unopened bags have a shelf of 12 months.

SAFETY PROCEDURES

Wear safety such as rubber gloves, dust mask and safety glasses used to handle conventional cement based products should be worn. In case of contact with eyes, rinse with plenty of water and seek medical advice accordingly.

TECHNICAL ASSISTANCE

For advice on how to use ATLAS TILE GROUT products consult your nearest SALINA technical office.

Dubai

United Arab Emirates
Tel: +971 4 3232935
Fax: +971 4 3232936
P.O.Box 32143

Riyadh

Saudi Arabia
Tel: +966 1 4984266
Fax: +966 1 4984277
P.O.Box 5590 ZIP 11432

Sharjah

United Arab Emirates
Tel: +971 6 7434488
Fax: +971 6 7434484
P.O.Box 23872

Cairo

Egypt
Tel: +20 55 2642048
Fax: +20 55 2574776
P.O.Box 911 Heliopoes

Abu Dhabi

United Arab Emirates
Tel: +971 2 6782206
Fax: +971 2 6783058
P.O.Box 70148

Mississauga

Ontario, Canada
Tel: +1 647 984 6479
Fax: +1 905 232 4720
P.O.Box 958 Summerbreeze
Crt. L5V 1C9

COLORS

- » White
- » 28 Vibrant Colors

FEATURES

- » Excellent adhesion.
- » Crack free joints.
- » Clear fade resistant color.
- » Easy to Use.

USES

- » General purpose colored grout for use with tile joints below 5mm width.
- » Interior and Exterior application.

PACKAGING

ATLAS TILE GROUT is packaged 10kg, it can be custom packaged to suit specific job requirements

TECHNICAL DATA

Physical State	Solid Powder
Binder	Portland Cement
Color	28 Vibrant Colors
Granular Size	0 – 0.2 mm
Water Requirement	30 % Approx.*
Yield	700 Lit./ Ton approx.*
Working Time	30 Min.*
Dry Density	1.35 Kg/L*
Compressive strength	20 N/mm ² @ 28 Days*
Flexural Strength	5 N/mm ² @28 days*
Bond Standards	1.2 N/mm ² @14Days
Curing	2 days @ 3 times/day
Shelf Life	12 Months from Mfg. Date

* Test results as per laboratory condition